

Instruction Sheet

Model D3276

Spray Gun

INTRODUCTION

The SHOP FOX® Spray Gun features a 1.5mm nozzle and 750cc paint canister that offers consistent spray patterns and fast coverage.

SETUP

The Model D3276 accepts 1/4" NPT connectors. Mount an air regulator as close as possible to the spray gun. Use the adjustment knob on the regulator to set your working air pressure between 65-85 PSI.

ADJUSTMENTS

See **Figure 1** to identify the location of the spray gun controls and adjust in the following order:

- **1.** *Nozzle Control*—Adjusts the spray pattern from vertical to horizontal.
- **2.** *Pattern Control*—Variably adjusts the spray pattern from round to a wide fan.
- **3.** *Fluid Control*—Adjusts how far back the trigger can be pulled, which affects the volume of paint released.

OPERATIONS

Hold the sprayer 8"-10" from the workpiece, and keep the spray gun perpendicular to the workpiece during strokes. *DO NOT pivot your wrist when spraying!*

MAINTENANCE

- 1. Clean the spray gun by flushing it with thinner. DO NOT immerse the gun in the thinner!
- 2. To avoid internal damage, clean the air cap with the supplied brush.




Figure 1. Model D3276.






CUSTOMER SERVICE

For questions contact Woodstock International Technical Support at (360) 734-3482, or send email to: tech-support@shopfox.biz.

COPYRIGHT @ BY WOODSTOCK INTERNATIONAL, INC.

WARNING: NO PORTION OF THIS DOCUMENT MAY BE REPRODUCED IN ANY SHAPE OR FORM WITHOUT THE WRITTEN APPROVAL OF WOODSTOCK INTERNATIONAL, INC. SEPTEMBER 2003, PRINTED IN CHINA.

D3276 Parts Diagram



REF	PART #	DESCRIPTION
1	XD3276001	AIR CONNECTOR
2	XD3276002	GUN BODY
3	XD3276003	O-RING
4	XD3276004	RECTANGULAR WASHER
5	XD3276005	AIR INLET VALVE
6	XD3276006	SWITCH SPRING
7	XD3276007	O-RING
8	XD3276008	PACKING SEAT
9	XD3276009	FLUID ADJ. KNOB
10	XD3276010	NEEDLE SPRING
11	XD3276011	NEEDLE SET 1
12	XD3276012	NEEDLE SET 2
13	XD3276013	SEALING UNIT
14	XD3276014	STOP RING
15	XD3276015	PATTERN ADJ. SEAT
16	XD3276016	O-RING
17	XD3276017	PATTERN ADJ. KNOB
18	XPEC02M	E-RING 4MM

	KD3276019 KD3276020	TRIGGER TRIGGER PIN
20 X		TRIGGER PIN
	/D227/024	
21 X	KD3276021	DIRECTION SCREW
22 X	KD3276022	SPACER
23 X	KD3276023	O-RING
24 X	KD3276024	NOZZLE
25 X	KD3276025	GASKET FOR AIR CAP
26 X	KD3276026	AIR CAP SET
27 X	KD3276027	ROUND NUT
28 X	KD3276028	PAINT INLET PLUG
29 X	KD3276029	FEMALE CONNECTOR
30 X	KD3276030	PAINT-IN NOZZLE
31 X	KD3276031	SMALL SPACER NUT
32 X	KD3276032	LID
33 X	KD3276033	GASKET
34 X	KD3276034	SUCTION TUBE
35 X	KD3276035	ALUMINUM CUP
36 X	KD3276036	CUP RIVET